

RECEIVED  
CENTRAL FAX CENTER  
DEC 29 2006

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in this application:

**LISTING OF CLAIMS:**

1. (Currently Amended) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

at least one sensor configured to detect at least one predetermined open position of the spare-wheel carrier and to transmit the at least one predetermined open position to a control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with ~~the position of~~ detection of the spare-wheel carrier in the predetermined open position.

2. (Original) The spare-wheel carrier according to claim 1, further comprising a display unit configured to represent a position of the spare-wheel carrier.

3. (Previously Presented) The spare-wheel carrier according to claim 2, wherein the display unit is arranged in an instrument cluster.

4. (Original) The spare-wheel carrier according to claim 1, wherein the spare-wheel carrier is lockable.

5. (Previously Presented) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with the position of the spare-wheel carrier,

wherein the sensor includes a lock having a touch-sensitive switch configured to detect the position of the spare wheel carrier, the lock configured to retain the position of the spare-wheel carrier.

6. (Original) The spare-wheel carrier according to claim 5, further comprising an actuator assigned to the lock, the actuator operable in accordance with a grip switch.

7. (Original) The spare-wheel carrier according to claim 5, wherein the lock includes at least one locking element, including a striker having a ball and a pin, and at least one complementary locking element, including at least two swivelable ball sockets, one of the at least one locking element and the at least one complementary locking element attached to the body of the motor vehicle, another one of the at least one locking element and the complementing locking element attached to the spare-wheel carrier.

8. (Original) The spare-wheel carrier according to claim 7, wherein the ball supports the striker.

9. (Original) The spare-wheel carrier according to claim 7, wherein the complementary locking element includes a movable blocking part configured to block swivel of the ball sockets from a closed position into an open position and configured to release the locking element in accordance with at least one of displacement and tilt of the blocking part.

10. (Original) The spare-wheel carrier according to claim 7, further comprising a catch hook configured to hold the ball sockets in a closed position in accordance with a weight of the catch hook.

11. (Original) The spare-wheel carrier according to claim 7, wherein the locking element includes at least one lever arranged as a release mechanism.

12. (Original) The spare-wheel carrier according to claim 7, wherein the lock includes an emergency release device configured to manually release the spare-wheel carrier, the emergency release device including an emergency release lock including a striker having at least one rotatable actuator rotatable into at least one unlocked position and a locked position, in the unlocked position, at least one first lever arranged to release the spare-wheel carrier movable in accordance with

displacement of the striker, in the locked position, the at least one first lever not movable in accordance with displacement of the striker.

13. (Original) The spare-wheel carrier according to claim 12, wherein the emergency release device includes at least one second lever positioned to operate the at least one first lever.

14. (Previously Presented) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

- at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with the position of the spare-wheel carrier;

- at least one bearing arranged on the body; and
- an end switch assigned to the at least one bearing.

15. (Original) The spare-wheel carrier according to claim 14, further comprising a grip switch assigned to the tailgate, the tailgate operable by the end switch as a function of the detected position of the spare-wheel carrier.

16. (Previously Presented) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

- at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with the position of the spare-wheel carrier; and

- an arrangement configured to block operation of a rear window in accordance with lock of the spare-wheel carrier.

17. (Currently Amended) A device, comprising:  
a tailgate of a motor vehicle;

a spare-wheel carrier pivotably arranged at a body of the motor vehicle and arranged in a region of the tailgate;

a control unit; and

at least one sensor configured to detect at least one predetermined open position of the spare-wheel carrier and to transmit the at least one predetermined open position to the control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with ~~the position of~~ detection of the spare-wheel carrier in the predetermined open position.

18. (Currently Amended) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

means for detecting at least one predetermined open position of the spare-wheel carrier;

means for enabling and blocking functions of the motor vehicle in accordance with ~~the position of~~ detection of the spare-wheel carrier in the predetermined open position; and

means for transmitting the predetermined open position of the spare-wheel carrier from the detecting means to the enabling and blocking means.

19. (Currently Amended) A method, comprising:

detecting at least one predetermined open position of a spare-wheel carrier on a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle; and

enabling and blocking functions of the motor vehicle in accordance with the ~~position of~~ detection of the spare-wheel carrier in the predetermined open position.